

扬州三菱电子有限公司
规格书

客户

型号

MDC380B

地址：江苏省扬州市南通西路 6 号

电话：0514-87344294

传真：0514-87310017

E— mail: SL you and me @ 163.com

<http://www.YZSLDZ.com>


MDC380B 技术资料

特点:

- 金属化三氧化二铝陶瓷绝缘, 传热性好。
- 高温焊料焊接, 有利于可靠性。

典型应用:

- 变频器
- 开关电源
- 电焊机



MDC

V_{RSM} (V)	V_{RRM} (V)	I_F (AV) =380A (sin 180° Tc=100°C)
900	800	MDC380B-8
1300	1200	MDC380B-12
1700	1600	MDC380B-16
1900	1800	MDC380B-18
2100	2000	MDC380B-20
2500	2400	MDC380B-24

I_F (AV)	Tc=100°C, 正弦半波	380	A
I_{FSM}	Ta=25°C, 10ms, 0.6V _{RRM}	13000	A
I^2t	Ta=25°C, 10ms	0.005 × 13000 ²	A ² S
V_{FM}	I _{FM} =1140A, Ta=25°C	1.20	V
V_{FO}	Tj=150°C	0.78	V
r_F	Tj=150°C	0.36	mΩ
I_{R1}	Ta=25°C, V _{RRM}	50	μA
I_{R2}	Ta=150°C, V _{RRM}	8	mA
Rjc		0.05	°C/W
Rcs		0.04	°C/W
Tstg		-40~+150	°C
Viso	Ac,50HZ,正弦波,1min	2500	V
Ms	散热器安装力矩	5 ± 15%	N•m
Mt	电极端子安装力矩	12 ± 10%	N•m

